



Tapered Roller Bearing

d 44,450-45,618mm 1,7500-1,7960 in-25580/25520/Q

参数信息:



Principal dimensions ( mm ) :

|     |        |
|-----|--------|
| d : | 44.45  |
| D : | 82.931 |
| T : | 23.812 |

Basic load ratingskN :

|          |      |
|----------|------|
| dycCr :  | 80.9 |
| stcCor : | 106  |
| Pu :     | 11.8 |

Speed ratingsrpm :

|                  |               |
|------------------|---------------|
| Speed Ratings :  | 6000          |
| Limiting Speed : | 9000          |
| Weight :         | 0.57          |
| Designation :    | 25580/25520/Q |
| Series :         | 25500         |

Dimensions mm :

|         |       |
|---------|-------|
| d :     | 44.45 |
| d ~ :   | 62.1  |
| B :     | 25.4  |
| C :     | 19.05 |
| r Min : | 3.5   |
| r Min : | 0.8   |
| a :     | 17    |

Abutment and fillet dimensions mm :

|          |      |
|----------|------|
| d Max :  | 53   |
| d Min :  | 55.5 |
| Da Min : | 71   |
| Da Max : | 76   |

Db Min : 76

Ca Min : 5

Cb Min : 4.5

r Max : 3

r Max : 0.8

Value :

e : 0.33

Yo : 1.8

: